



Note 1: Suggested Maximum Torque: 28.25 N-cm
 While this value is provided from reliable sources, there are many variables that will effect this value and the use of this information is at the sole risk of the user.

TITLE: MS-IMU3020 Dimensional Drawing Metric Rev D			
UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN MM		DRAWN	JB 04/04/19
TOLERANCES		ENG APPR.	DL 04/04/19
ANGULAR: MACH \pm 0.1		MFG APPR.	EL 04/04/19
TWO PLACE DECIMAL \pm 0.25		DOC NO	
THREE PLACE DECIMAL \pm 0.076		REV	
FOUR PLACE DECIMAL \pm 0.0127		DOC00449 C	
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2009		PART NO	
MATERIAL 6061-T6 AL		MP00062 D	
FINISH MIL-A-8625 ANODIZE		SCALE: 2:1 WEIGHT: SHEET 1 OF 1	
DO NOT SCALE DRAWING			



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEMSENSE, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEMSENSE, LLC IS PROHIBITED.