



**Note 1:** Suggested Maximum Torque: 28.25 N-cm  
 While this value is provided from reliable sources, there are many variables that will effect this value and the use of this information is at the sole risk of the user.

TITLE: MS-IMU3025 Dimensional Drawing Metric			
UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES		DRAWN	JB 04-05-2019
<b>TOLERANCES</b>		ENG APPR.	DL 04-05-2019
ANGULAR: MACH $\pm 0.1$		MFG APPR.	EL 04-05-2019
TWO PLACE DECIMAL $\pm 0.25$		DOC NO DOC00734	
THREE PLACE DECIMAL $\pm 0.076$		REV A	
FOUR PLACE DECIMAL $\pm 0.0127$		REV A	
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2009		SCALE: 2:1	
MATERIAL	6061-T6 AL	PART NO	MP00075
FINISH	MIL-A-8625 ANODIZE	WEIGHT:	
DO NOT SCALE DRAWING		SHEET 1 OF 1	



**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEMSENSE, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEMSENSE, LLC IS PROHIBITED.